

DEPOSIT SAFE

TYPE EURO II, III



Use

The Deposit Safe is available to receive cash deposits round the clock. No access to the key or pincode for the safe is needed. The system is particularly useful and rational where large sums of cash are handled by a number of people also outside normal working hours i.e. shops, supermarket and petrol stations.

Description

The Deposit Safe is a Euro tested safe as per 1143 in Grade II and a Deposit unit, which is an integral part of the safe and has the same protective material as the safe itself.

Locking

As standard the Safe is provided with a changeable keylock type FAS/S&G 6890.

Available as option: Combination lock type S&G 8550 MP.

Electronic combination lock: Mas Hamilton, ComboGard alt. Comptronic.

Finish

Light grey, RAL 9002.

Anchoring

All models are prepared for base anchoring

Weight and measurements

See overleaf.

Dimensions in mms and kilos

EURO II

Model	D55	D70	D100
External measurement mm	770	920	1220
Height	480	480	510
Width	480	480	480
Depth			
Internal measurements mm	390	540	840
Height	360	360	390
Width	300	300	300
Depth			
Dimensions of the deposit opening mm	55	55	55
Height	225	225	225
Width	150	150	150
Depth			
Weight, kilo	350	400	540

EURO III

Model	D70	D100	D120	D140
External measurements mm	920	1220	1420	1620
Height	520	600	600	700
Width	520	550	550	600
Depth				
Internal measurements mm	520	820	1020	1220
Height	360	440	440	540
Width	300	330	330	380
Depth				
Dimensions of the deposit opening mm	55	55	55	55
Height	225	225	225	225
Width	150	150	150	150
Depth				
Weight, kilo	590	800	900	1190

OPTIONAL LOCKING:

Only to the safe door



Electronic pincode lock



Combination lock

We reserve the right to alter the specification without prior notice



Head office

Robur Safe AB

Lundbyvägen 8

SE-310 50 SÖLÖNGE, SWEDEN

Tel: +46 346 260 260

Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com